

KSIX Electric car charger Policharger KSIX IN-SC, 7.4kW, Single-phase, Type 2 female connector

DESCRIPTION

Our EVHOME+SC Policharger KSIX car charger is here to stay. This charger, manufactured and developed in collaboration with Policharger, is easy to install and offers extremely simple and intuitive use to optimise electric vehicle charging. Sensor for dynamic power management not included. The power adjustment is done manually via the display menu or the keypad.

The EVHOME+SC Policharger KSIX charger is a single-phase charger up to 7.4 kW with T2 female socket connector. It is compatible with all vehicles with Type 2 and Type 1 connector (T1-T2 adapter cable). Includes password and key combination locking system.

Hourly power programming

Program the power according to the schedule (off-peak and peak) and optimise the charging process of your vehicle.

Dynamic power regulation

The Policharger KSIX charger allows you to adjust the charging power up to 7.4 kW at any time via the display menu or keypad to suit the charging needs of any vehicle. Does not include power meter (toroidal clamp).

LCD display

Keypad panel menu with LCD display that provides information about charging intensity, energy consumed and charging status information.

Wide compatibility

Female T2 socket connector model, compatible with all electric cars on the market using the T2-T2 and T2-T1 adapter cables.

Maximum durability

Designed and tested to guarantee maximum resistance and endurance: the KSIX Policharger KSIX charger allows optimal operation both indoors and outdoors.

Locking system

This charger incorporates an intuitive password and key combination locking system to ensure maximum security.

TECHNICAL SPECIFICATIONS.

| Weight | 3 kg |
|-----------------|-------------------|
| Dimensions | 229 x 203 x 99 mm |
| Compatibility | All models |
| Frequency range | 50Hz - 60Hz |





| Degree of protection | IP54 |
|----------------------|--|
| Power | 7.4kW |
| Connector type | Type 2 female |
| Working conditions | Operating temperature: -20° C - 40° C |
| Reference directives | 2014/35/EU, IEC61851-1, IEC61851-22, IEC62196-1 |
| Input power | 230 ± 10 %, 1P+N+PE |
| Impact resistance | IK10 |

STRENGTHS

ISIX REF. BXWALLPOLINSP EAN: 8427542121895

Recommended retail price: €600.00