

Wallbox Kit Copper SB electric charger, type 2, 22kW + Powerboost 3 phase 65A/EM340, 5m, Black

DESCRIPTION

Copper SB

Charging power up to 22kW (3 Phase)

Compatible with all Type 1 and Type 2 electric cars

Technical information

Connector type: Socket

Maximum current: 32 A, 5x10 mm² cable

DC Leakage protection Included: Yes

User interface: myWallbox Portal, Wallbox App

Overvoltage Category: CAT III

Storage temperature: From -40°C to 70°C

RCCB: Requires an external RCCB

Nominal frequency: 50 Hz / 60 Hz

Degree of protection: IP54 / IK08

Operating temperature From -25 °C to 40 °C

Input voltage: $110 / 230 \text{ V AC} \pm 10\% (1P) / 400 \text{ V AC} \pm 10\% (3P)$

Included features: Power Sharing Smart

Dimensions: 260x192x113 mm

Charging power: 22kW

Charging mode Mode 3

Charger status information: Wallbox App, myWallbox Portal, RGB LED, Pantalla

de 10.9 cm (4.3")

Cable length: 5m

Important note

If you are a Renault Zoe I (2015 edition) user, please keep in mind that this model is only compatible with this charger for single-phase charging (up to 7.4kW).

The Renault Zoe II (2018 edition), ordered after the 19th of March 2018, is perfectly compatible with this charger for both singe-phase and three-phase charging (up to 22kW).

Charging cable holder

Wallbox charging cable holder compatible with Commander 2, Copper SB, Pulsar Plus and Pulsar chargers.







Charging cable with connector, 5 meters length, compatible with all electric cars and chargers with Type 2 connector.

- This charging cable is compatible with all electric cars and chargers with Type 2 connector
- Charging power up to 22 kW
- Cable length 5 m
- Charging cable Mode 3
- Single-phase and three-phase AC cable
- Includes covers for connectors
- Compatible with Copper SB, KSIX EVHome+ SC and all public applications with Type 2 socket

TECHNICAL SPECIFICATIONS.

Black Color IP54 Degree of protection 22kW Power Type 2 Connector type IK08 Impact resistance Yes **Power Sharing** yes Wireless. Wifi Yes yes Ethernet 3G/4G yes 260 x 192 x 113 mm Measures yes OCPP

STRENGTHS